

Z-Wave Light & Light Dimmer Switch Series

Living Smart with Easy Lighting Control

- Automatic and remote control of lights & dimmers
- Two-way or three-way control
- Grounding and Non-Grounding Light Switch versions
- Single or Double Light & Dimmer Light switches
- European-style and American-style rocker paddle switches or touch pad control switches
- Compatible with other manufacturers' Z-Wave systems

The Z-wave Light and Dimmer Light Switch Series ushers in wireless lighting control that plays a key role in energy management, and enhancing the convenience, comfort, safety of smart homes and businesses. The Light Switch series replaces any standard light switch, giving the users the freedom to use whatever light bulb they require, or if the fixture requires bulbs of a particular size, shape or style that are not compatible with smart bulbs.

The Z-Wave Light and Dimmer Light Switches are compatible with other manufacturers' Z-Wave systems and be can flexibly integrated into new or existing Z-Wave home automation or security systems, allowing for remote management, and customized schedules or scenes.

Users can schedule tasks as simple such as turning lights on after dark or before their kids come home from school, or turning specific lights off every day at a specific time to reduce power consumption. Enjoy complete control of your lighting whether you are at home or on the go. Creating a green home has never been easier!



American-Style
Rocker Switch



European-Style
Rocker Switch



American-Style
Touch Switch



European-Style
Touch Switch

Z-Wave Light Switch Series

Features and Specifications

LS-1A/E-G-ZW

Grounding Light Switch Series



LS-1A-G-ZW



LS-1E-G-ZW

	LS-1A-G-ZW (Americas)	LS-1E-G-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module	
Frequency	908.42MHz (US) / 868.42MHz (EU)	
Power	110V ~ 230V, 50/60Hz	
Maximum Load	5A	
Load Types	Supports Incandescent, CFL, Tungsten, LED lighting devices	
Electrical Requirements	Single-Pole or 3-way switch; Connects to Neutral, Load, Line, and Traveler wires	
User Interface Type	Rocker Paddle	
Operating Temperature	-10°C to 45°C (14°F to 113°F)	
Operating Humidity	Up to 85% non-condensing	
Dimensions	120mm x 70mm x 50mm	84mm x 84mm x 47.35mm

LS-1A/E-3W-ZW

Three-Way Light Switch Series (One Main Switch and One Auxiliary Switch)



LS-1A-3W-ZW



LS-1E-3W-ZW

	LS-1A-3W-ZW (Americas)	LS-1E-3W-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module	
Frequency	908.42MHz (US) / 868.42MHz (EU)	
Power	110V ~ 230V, 50/60Hz	
Maximum Load	5A	
Load Type	Supports Incandescent lighting devices	
Electrical Requirements	3-way switch; Connects to Neutral, Traveler, Load, and Line wires (Master Switch); Connects to Traveler and Line wires (Slave Switch)	
User Interface Type	Rocker Paddle	
Operating Temperature	-10°C to 45°C (14°F to 113°F)	
Operating Humidity	Up to 85% non-condensing	
Dimensions	120mm x 70mm x 50mm	84mm x 84mm x 47.35mm

Z-Wave Double Light Switch Series

Features and Specifications

LS-2A/E-G-ZW

Double Light Switch Touch Pad Control -- Grounding Light Switch Series



	LS-2A-G-ZW (Americas)	LS-2E-G-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module	
Frequency	908.42MHz (US) / 868.42MHz (EU)	
Power	100V ~ 240V, 50/60Hz	
Maximum Load	5A	
Load Types	Supports Incandescent, CFL, Tungsten, LED lighting devices	
Electrical Requirements	DoublePole switch; Connects to Neutral, Loads and Line wires	
User Interface Type	Touch Pad	
Operating Temperature	-10°C to 45°C (14°F to 113°F)	
Operating Humidity	Up to 85% non-condensing	
Dimensions	120mm x 70mm x 50mm	84mm x 84mm x 47.35mm

LS-2A/E-B-ZW

Double Light Switch Touch Pad Control -- Non-Grounding Light Switch Series



	LS-2A-B-ZW (Americas)	LS-2E-B-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module	
Frequency	908.42MHz (US) / 868.42MHz (EU)	
Backup Battery	3.6V 200mAh Rechargeable Battery x1	
Battery Backup Time	6 days	
Power	110V ~ 230V, 50/60Hz	
Maximum Load	5A	
Load Types	Supports Incandescent lighting devices	
Electrical Requirements	DoublePole Switch; Connects to Loads, and Line wires	
User Interface Type	Touch Pad	
Operating Temperature	-10°C to 45°C (14°F to 113°F)	
Operating Humidity	Up to 85% non-condensing	
Dimensions	120mm x 70mm x 50mm	84mm x 84mm x 47.35mm

Z-Wave Light Dimmer Switch Series

Features and Specifications



LSD-1A-ZW LSD-1E-ZW

LSD-1A/E-ZW

Light Dimmer Switch Touch Pad Control -- Grounding Light Switch Series

	LSD-1A-ZW (America)	LSD-1E-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module	
Frequency	908.42MHz (US) / 868.42MHz (EU)	
Power	95V ~ 265V, 50/60Hz	
Maximum Load	2.5A	
Load Type	Supports Incandescent and Dimmable LED lighting devices	
Electrical Requirements	Single-Pole switch; Connects to Neutral, Load, and Line wires	
User Interface Type	Touch Pad	
Operating Temperature	-10°C to 45°C (14°F to 113°F)	
Operating Humidity	Up to 85% non-condensing	
Dimensions	120mm x 70mm x 50mm	84mm x 84mm x 47.35mm

LSD-2E-ZW

Double Light Dimmer Switch Touch Pad Control -- Grounding Light Switch Series



LSD-2E-ZW

	LSD-2E-ZW (Europe)
Communications Protocol	Z-Wave Plus 500 series module
Frequency	868.42MHz (EU)
Power	230V/60Hz
Maximum Load	2.5A
Load Type	Supports Incandescent and Dimmable LED lighting devices
Electrical Requirements	Single-Pole switch; Connects to Neutral, Loads, and Line wires
User Interface Type	Touch Pad
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	84mm x 84mm x 47.35mm

Z-Wave Light & Light Dimmer Switch Series

Ordering Information

North American-Style Light & Light Dimmer Switch Series

LS-1A-G-ZW	Grounding light switch
LS-1A-B-ZW	Non-grounding light switch
LS-1A-3W-ZW	Three-way light switches consisting of a main switch and an auxiliary switch
LS-2A-G-ZW	Grounding double light switch touch pad control
LS-2A-B-ZW	Non-grounding double light switch touch pad control
LSD-1A-ZW	Grounding light dimmer switch touch pad control

European-Style Light & Light Dimmer Switch Series

LS-1E-G-ZW	Grounding light switch
LS-1E-B-ZW	Non-grounding light switch
LS-1E-3W-ZW	Three-way light switches consisting of a main switch and an auxiliary switch
LS-2E-G-ZW	Grounding double light switch touch pad control
LS-2E-B-ZW	Non-grounding double light switch touch pad control
LSD-1E-ZW	Grounding light dimmer switch touch pad control
LSD-2E-ZW	Grounding double light dimmer switch touch pad control